

LITEGUARD

FEATURES & BENEFITS

LITEGUARD

MIGHTYGUARD

ULTRAGUARD

XTREMEGUARD

POLYURETHANE

High-quality material provides strength and durability equating to extremely high load-bearing capabilities and resistance to chemical substances.

FLUSH HINGES

Less failure from continued use.

HINGE PIN


Reinforced fiberglass rod provides durability & strength to lid hinge, which will never corrode, rust or break.

1" & 1.25" CHANNEL SIZES AVAILABLE



LIGHTWEIGHT CONSTRUCTION WITH BUILT-IN HANDLES

Reduced shipping costs and less fatigue with handling.



OPERATING TEMPERATURE

Safely withstands extreme conditions ranging from -40°F to 120°F.



MAINTENANCE

No painting or maintenance required; holds up in all weather conditions.



ELASGLOW TECHNOLOGY AVAILABLE

Glow-in-the-dark strips illuminate low light environments.



SMOOTH HAMMER INTERLOCK DESIGN

Strong connections and easy installation.



NON-SLIP SURFACE DESIGN

Safer use for pedestrian traffic at facilities, public events or job sites.



SAFETY COLOR SCHEME

Eye-catching colors ensure safety.



SURFACE PATTERN

Tread pattern designed for stability to minimize trips and falls.



COMPLIANT

Compliant with safety regulations including NEC, OSHA, REACH & RoHS.



LIFETIME
WARRANTY

TRAFFIC SAFETY WAREHOUSE

The Best in Safety for Less

TrafficSafetyWarehouse.com

(847) 966-1018