

XTREMEGUARD

FEATURES & BENEFITS

LITEGUARD

MIGHTYGUARD

ULTRAGUARD

XTREMEGUARD

UP TO 4.5" CHANNEL SIZES

POLYURETHANE

High-quality material provides strength and durability equating to extremely high load-bearing capabilities and resistance to chemical substances.

FLUSH HINGES

Less failure from continued use.

HINGE PIN

Reinforced fiberglass rod provides durability & strength to lid hinge, which will never corrode, rust or break.

LIGHTWEIGHT CONSTRUCTION WITH BUILT-IN HANDLES

Reduced shipping costs and less fatigue with handling.

OPERATING TEMPERATURE

Safely withstands extreme conditions ranging from -40°F to 120°F.

MAINTENANCE

No painting or maintenance required; holds up in all weather conditions.

ELASGLOW TECHNOLOGY AVAILABLE

Glow-in-the-dark strips illuminate low light environments.

SMOOTH HAMMER INTERLOCK DESIGN

Strong connections and easy installation.

SAFETY COLOR SCHEME

Eye-catching colors ensure safety.

PATENTED GULLWING DESIGN

Additional weight support for extreme use.

SURFACE PATTERN

Tread pattern designed for stability to minimize trips and falls.

COMPLIANT

Compliant with safety regulations including NEC, OSHA, REACH & RoHS.

NON-SLIP SURFACE DESIGN

Safer use for pedestrian traffic at job sites such as active mines.

LIFETIME WARRANTY

ELASCO
PRODUCTS
elascoproducts.com
800-827-7887

XTREMEGUARD

FEATURES & BENEFITS

LITEGUARD

MIGHTYGUARD

ULTRAGUARD

XTREMEGUARD



12' W RAMPS PROVIDE GRADUAL SLOPE

Better support for equipment in mining applications and other job sites.

MODULAR DESIGN FOR INCREASED PROTECTION

Use multiple ramps together; additional 6" channel and lid available.

6" CHANNEL SIZE



POLYURETHANE

High-quality material provides strength and durability equating to extremely high load-bearing capabilities and resistance to chemical substances.



SAFETY COLOR SCHEME

Eye-catching colors ensure safety.



SURFACE PATTERN

Tread pattern designed for stability to minimize trips and falls.



COMPLIANT

Compliant with safety regulations including NEC, OSHA, REACH & RoHS.



NON-SLIP SURFACE DESIGN

Safer use for pedestrian traffic at job sites such as active mines.



CONNECTION SUPPORT

Two sides interlock with fiberglass rod.

TWO 6", TWO 4" AND TWO 3" CHANNELS



LIFETIME WARRANTY



ELASCO
PRODUCTS

elascoproducts.com

800-827-7887