# Pedestrian / Warning Signs



Pedestrian/Warning LED Signs

#### Solar / AC Powered

#### Warning Series Model

## **Specifications**

Construction	.080 Highway Grade Aluminum / Stainless Fasteners
Reflective Sheeting	Type IX Reflective Sheeting
	Fluorescent Yellow Green Sheeting
Circuitry Technology	Sealed PCB Technology
	Micro-Controller Circuitry
	24 Hour Operation
	50 to 60 Times Minute Flash Rate
Solar/AC/Battery	15 - 20 Watt Polycrystalline Solar Cell
Specifications	6 - 12 Volt SLA Battery (3 to 4-year battery life)
(Depending on Model)	AC Power (Up to 264 Volts)
LED Lighting	8 - G2 LED Lights in Sign Perimeter
	Cree High Power LED – Max 3.5 Watts
	Field Replaceable Grommet Mounted Lights
	Reflective LED Lighting (Patented)
Sizes	24" (4 LEDs ONLY) / 30" / 36" / 48" / 60"

Specifications subject to change without notice

### **Features**

- MUTCD Section 2A.07 / 2A.08 Compliant
- Flash Rate 50 to 60 Times per Minute
- Up to 25 Days of Operation Flashing 24 hours 7 days
- LED Life Expectancy over 100,000 hours
- White / Yellow LED Lights
- Multiple Mounting Hardware Options
- Keyed On / Off Switch
- Easy Battery Replacement in Field
- Quick LED Light Replacement

**Options:** Standard & Deluxe Timers / Wireless Activation-Communications
Push Button Activation



Warranty
10 Year Solar Collector Panel
5 Year Sign Construction
2 Year PCB/LED Technology
1 Year Battery



TrafficSafetyWarehouse.com (847) 966-1018