

ROCK-IT™ SIGN STAND

INSTRUCTIONS

1. Use one 3/8 x 5-1/2" hex bolt, and one locknut to secure plastic post to base.
Attach the post using the hole 11.5" from post bottom.
2. Use two 3/8 x 2-1/2 hex bolts, two washers, and two lock nuts to attach sign.
3. Add Vinyl Cap to the top of the Power Post to help prevent water from entering.
4. Fill Base.

IMPORTANT! Insert Post In Base and Secure Post Upright Before Filling

Rock-It 18 Filling Options:

1. Dry Sand - holds up to 125 lbs.
 2. H2OLD Base Gel + 8 Gallons of Water
- Both options are good for freezing temperatures

DO NOT FILL WITH WATER ONLY

Recommend only filling up to 80 lbs. if planning to move after filling

Rock-It 24 Filling Options:

1. Dry Sand - holds up to 224 lbs.
 2. H2OLD Base Gel + 14 Gallons of Water
- Both options are good for freezing temperatures

DO NOT FILL WITH WATER ONLY

When using gel in areas with freezing temperatures, DO NOT FILL TO CAPACITY!

Allow for gel to expand when frozen.


Recommend only filling up to 80 lbs. if planning to move after filling.



Scan For Video
Instruction

Hardware Provided:

- 1 ea. Hex Bolt Zinc 3/8 x 5-1/2
- 2 ea. Hex Bolt Zinc 3/8 x 2-1/2
- 2 ea. Washer 3/8
- 3 ea. Locknut 3/8-16
- 1 ea. Vinyl Cap



PLASTICADE®

Plasticade.com

Part #8279 Rev. 6