

SPEED BUMP: VR-206-7M

When designing parking lots, it is important to ensure both pedestrian and driver safety. Using bumps, humps and parking stops can increase customer safety while limiting potential damage. Speed bumps and humps ensure that drivers decrease their speed in high-traffic areas, and are easily transported to wherever they may be needed. They are made from durable molded rubber that will withstand extreme temperatures. The speed bumps and humps include a textured surface, making them safe to use in inclement weather. They can also be used in construction areas to help slow down traffic while keeping workers safe. The speed bumps are easily set up wherever you need decreased traffic speeds.



FEATURES

- Made of durable, molded rubber
- Perfect for indoor or outdoor use
- Able to withstand extreme temperatures without cracking or drying out
- Features eight reflective eyelets and eight mounting holes
- Grooved surfaces ensure grip and traction even in adverse weather conditions
- Capable of combining multiple middle pieces together to create length required

SPECIFICATIONS

- Rubber speed bump middle section with one half yellow and one half black (End pieces sold separately)
- Weight: 35lbs/15.88kg
- Height: 2"/0.58cm
- Length: 39.25"/99.69cm
- Width: 13.5"/34.29cm
- 8 holes molded in the product for mounting to various surfaces
- Holes are located 4 7/8" on center from each end, then 9 7/8" apart center to center
- Holes are 2 3/8" to center of long edge

ADDITIONAL PRODUCTS

- Various fastener systems used for mounting to different surfaces: FS-1, FS-2 and FS-3
- Corresponding end pieces: VR-206-7E (sold separately)